

Subminiature PCB Power Relay

PC435



FEATURES

- 10 Amp continuous contact capacity
- 1 Form A & 1 form C contact forms
- Subminiature design
- Class "B" insulation standard
- Sensitive version available
- 4 Kv dielectric between coil and contacts
- 8mm spacing between contacts and coil
- Sealed, immersion cleanable
- Lead Free & RoHS Compliant

cRU US File # E93379

UL/CUR RATINGS

Load Type	Normally Open Contact	Normally Closed Contact
General Use	10 Amps @ 125 VAC	5 Amps @ 125 VAC
	5 Amps @ 250 VAC	3 Amps @ 250 VAC
	5 Amps @ 30 VDC	3 Amps @ 30 VDC
	4.2 Amps @ 277 VAC	2 Amps @ 277 VAC
Motor	1/4 HP @ 250 & 277 VAC	—
Tungsten Lamp	TV-5	—

CONTACT DATA

Material		AgCdO (Silver Cadmium Oxide)
Initial Contact Resistance		100 milliohms max @ 0.1A, 6VDC
Service Life	Mechanical	1 X 10 ⁷ Operations
	Electrical	1 X 10 ⁵ Operations

CHARACTERISTICS

Operate Time	8 ms. Max.
Release Time	5 ms. Max.
Insulation Resistance	1000 megohms min, at 500VDC, 50%RH
Dielectric Strength	4000 Vrms, 1 min. between coil and contacts 1000 Vrms, 1 min. between open contacts
Shock Resistance	10 g, 11ms, functional; 100 g, destructive
Vibration Resistance	DA 1.6 mm, 10 - 55 Hz
Power Consumption	.45 W
Ambient Temperature Range	-40 to 70 C operating for class B, -40 to 130 C storage
Weight	7 grams approx.

ORDERING INFORMATION

Example:	PC435	-1C	-12	S	F	-H	-X
Model:	PC435						
Contact Form:	1A, 1C						
Coil Voltage:	3, 5, 6, 9, 12, 24, 48						
Enclosure:	S: Sealed; C: Flux Free						
Insulation System:	Nil: Class B (125 degrees C), F: Class F (155 degrees C)						
Coil Sensitivity:	Nil: Standard .45 W, H: Sensitive .2 W						
RoHS Compliant:	-X						


Box Quantity: 2,000: Inner Box: 1,000

COIL DATA


Coil Voltage	Resistance ohms \pm 10%		Must Operate Voltage Max. (VDC)	Must Release Voltage Min. (VDC)
	Standard Coil	Sensitive Coil		
3	20	45	2.25	0.15
5	56	125	3.75	0.25
6	80	180	4.50	0.30
9	180	405	6.75	0.45
12	320	720	9.00	0.60
18	720	1620	13.50	0.90
24	1280	2880	18.00	1.20

Dimensions in Inches (millimeters)


Side View



End View



**Bottom View
PC Board Layout**



Wiring Diagram

